

Coffee Art C Touch

Daily Cleaning Instructions

- Read and follow the instructions carefully before you begin the daily cleaning procedure. This procedure should be performed on a daily basis or when prompted by the machine display.
 Never reach into the machine or under the coffee spout during the automatic cleaning cycle!
- When the "Start cleaning" message appears on the screen, follow the instructions to initial the clean cycle. **Note:** In some configurations, the machine will automatically initiate the cleaning cycle after two hours of the "Start cleaning" message appears. During that time all product buttons will be locked until the procedure is completed.
- (i) To order cleaning supplies please call 888.989.3004.



1. Use only Schaerer cleaning supplies for this procedure.




2. When the "Start cleaning" message appears on the upper left corner. Press and hold (3-5 seconds) the lower left corner of the touch screen to bring up service menu.



3. Select "Cleaning"



4. Insert cleaning tube. Press "Continue".





Coffee Art C Touch

Daily Cleaning Instructions



- **5.** Remove grounds bin. Empty coffee grounds into trash can. Wash, rinse, sanitize bin and set aside.
- i If grounds bin is not in place within 6 seconds, the machine will return to normal operating mode. If this happens, repeat step 2 and 3.



6. Remove metal shield above grounds bin and set aside.



7. Use large cleaning brush to wipe coffee grounds from brew unit and surrounding areas into drip tray. Do not touch brew unit or any other parts of inside area with your hands.



8. Put back metal shield and slide coffee grounds bin back into place.



 Lift dome lid and drop in one Schaerer cleaning tablet. Close lid after dropping tablet. Note: Dome lid is located behind front center hopper for 3 grinder machine confi guration.



10. Press "Ok" on the screen to activate cleaning cycle. Cleaning runs (4:33 min.)



Coffee Art C Touch

Daily Cleaning Instructions



11. Refill beans if necessary. Press "Finish" to return to normal operating mode.



12. Flush drip tray with a pitcher of water. Wipe the machine exterior thoroughly with a clean, damp cloth to remove residue.